

81 identifying a lexical container from among a plurality of lexical containers based on a length of the key, said lexical containers associated with respective key lengths and configured to hold respective maximum numbers of entries based on the respective key lengths; and searching the lexical container for an entry associated with the string based on the key, wherein at least one of the lexical containers is configured to hold a different number of entries than at least another one of the lexical containers.

2. (Not Amended) The method of claim 1, wherein the step of generating a key based on the string includes the step of compressing the string to produce the key.

3. (Not Amended) The method of claim 2, wherein the step of compressing the string to produce the key includes the step of performing an n-gram compression on the string.

4. (Not Amended) The method of claim 1, wherein the step of generating a key based on the string includes the step of using the string as the key.

5. (Amended) The method of claim 1, wherein the step of identifying a lexical container includes the steps of:

generating a prefix based on the key; and

identifying the lexical container from among the plurality of the lexical containers based on the length of the key and the prefix.

6. (Not Amended) The method of claim 1, wherein:

the step of identifying a lexical container based on a length of the key includes the step of identifying a hash table based on the length of the key, said hash table containing

sequences of slots for holding entries associated with strings, each of said sequences of slots corresponding to a respective hash value; and

the step of searching the lexical container for an entry associated with said string includes the steps of:

computing a hash value based on the key; and

searching the hash table based on the hash value for a slot holding an entry associated with said string.

7. (Not Amended) The method of claim 6, wherein the step of computing a hash value based on the key includes the step of computing the hash value based on the key and a prime number associated with the hash table.

8. (Not Amended) The method of claim 7, wherein the step of searching the hash table based on the hash value includes the steps of:

indexing one or more fixed regions of the hash table, each of the fixed regions having the prime number of slots, based on the hash value to identify one or more respective slots;

and

inspecting the one or more respective slots for a respective key value matching the key.

9. (Not Amended) The method of claim 8, wherein the step of searching the hash table further includes the step of searching for the key in a linked list of slots stored in an expansion region of the hash table, if the key was not found in the one or more respective slots for the key.

10. (Not Amended) The method of claim 6, further including the step of, if an entry for the string is not found at a first slot that corresponds to the hash value, but is found in a slot that

belongs to a sequence of slots that correspond to keys that produce said hash value, then moving a relative position of the entry for the string within the sequence of slots toward the beginning of the sequence of slots.

81 11. (Not Amended) The method of claim 6, further comprising the step of initializing a descriptor for the hash table, said descriptor storing a reference to the hash table and parameters for the hash table;

wherein the step of identifying a hash table includes the step of identifying a descriptor indicating the hash table and a prime number.

12. (Not Amended) The method of claim 11, wherein the step of initializing a descriptor for the hash table includes the step of initializing a prime number for use in computing a hash value.

13. (Not Amended) The method of claim 11, wherein the step of initializing a descriptor for the hash table includes the step of initializing a maximum number of slots for the hash table.

14. (Not Amended) The method of claim 11, wherein the step of initializing a descriptor for the hash table includes the step of initializing a maximum length of the sequences of slots for the hash table.

15. (Once Amended) A method of searching for a string in a lexical cache, comprising the computer-implemented steps of:

compressing the string to generate a key;

identifying a hash table from among a plurality of hash tables based on a length of the key,

said hash table containing sequences of slots for holding respective key values, each of

B1
said sequences of slots corresponding to a respective hash value and a number of slots being based on a respective key length, wherein at least one of the hash tables is configured to hold a different number of slots than at least another one of the hash tables; computing a hash value based on the key; using said hash value to locate a beginning of the particular sequence of slots that correspond to said hash value; searching the particular sequence of slots for a slot holding a key value matching the key; and if a slot having a key value matching the key is found in the particular sequence of slots, but is not at the beginning of said particular sequence of slots, then moving a relative position of the key value within the particular sequence of slots toward the beginning of the particular sequence of slots.

16. (Twice Amended) A computer-readable medium bearing instructions for searching for a string in a lexical cache, said instructions arranged, when executed by one or more processors, to cause the one or more processors to perform the steps of:

generating a key based on the string; identifying a lexical container from among a plurality of lexical containers based on a length of the key, said lexical containers associated with respective key lengths and configured to hold respective maximum numbers of entries based on the respective key lengths; and searching the lexical container for an entry associated with the string based on the key, wherein at least one of the lexical containers is configured to hold a different number of entries than at least another one of the lexical containers.

17. (Not Amended) The computer-readable medium of claim 16, wherein the step of generating a key based on the string includes the step of compressing the string to produce the key.

18. (Not Amended) The computer-readable medium of claim 17, wherein the step of compressing the string to produce the key includes the step of performing an n-gram compression on the string.

19. (Not Amended) The computer-readable medium of claim 16, wherein the step of generating a key based on the string includes the step of using the string as the key.

20. (Once Amended) The computer-readable medium of claim 16, wherein the step of identifying a lexical container includes the steps of:

generating a prefix based on the key; and

identifying the lexical container from among the plurality of the lexical containers based on the length of the key and the prefix.

21. (Not Amended) The computer-readable medium of claim 16, wherein:

the step of identifying a lexical container based on a length of the key includes the step of

identifying a hash table based on the length of the key, said hash table containing sequences of slots for holding entries associated with strings, each of said sequences of slots corresponding to a respective hash value; and

the step of searching the lexical container for an entry associated with said string includes the steps of:

computing a hash value based on the key; and

searching the hash table based on the hash value for a slot holding an entry associated with said string.

22. (Not Amended) The computer-readable medium of claim 21, wherein the step of computing a hash value based on the key includes the step of computing the hash value based on the key and a prime number associated with the hash table.

23. (Not Amended) The computer-readable medium of claim 22, wherein the step of searching the hash table based on the hash value includes the steps of:

indexing one or more fixed regions of the hash table, each of the fixed regions having the prime number of slots, based on the hash value to identify one or more respective slots;

and

inspecting the one or more respective slots for a respective key value matching the key.

24. (Not Amended) The computer-readable medium of claim 23, wherein the step of searching the hash table further includes the step of searching for the key in a linked list of slots stored in an expansion region of the hash table, if the key was not found in the one or more respective slots for the key.

25. (Not Amended) The computer-readable medium of claim 21, wherein said instructions are further arranged to cause the one or more processors to perform the step of, if an entry for the string is not found at a first slot that corresponds to the hash value, but is found in a slot that belongs to a sequence of slots that correspond to keys that produce said hash value, then moving a relative position of the entry for the string within the sequence of slots toward the beginning of the sequence of slots.

26. (Not Amended) The computer-readable medium of claim 21, wherein said instructions are further arranged to cause the one or more processors to perform the step of initializing a descriptor for the hash table, said descriptor storing a reference to the hash table and parameters for the hash table;

wherein the step of identifying a hash table includes the step of identifying a descriptor indicating the hash table and a prime number.

27. (Not Amended) The computer-readable medium of claim 26, wherein the step of initializing a descriptor for the hash table includes the step of initializing a prime number for use in computing a hash value.

28. (Not Amended) The computer-readable medium of claim 26, wherein the step of initializing a descriptor for the hash table includes the step of initializing a maximum number of slots for the hash table.

29. (Not Amended) The computer-readable medium of claim 26, wherein the step of initializing a descriptor for the hash table includes the step of initializing a maximum length of the sequences of slots for the hash table.

30. (Once Amended) A computer-readable medium bearing instructions for searching for a string in a lexical cache, said instructions arranged, when executed by one or more processors, to cause the one or more processors to perform the steps of:

compressing the string to generate a key;

identifying a hash table from among a plurality of hash tables based on a length of the key,

said hash table containing sequences of slots for holding respective key values, each of

B1

said sequences of slots corresponding to a respective hash value and a number of slots being based on a respective key length, wherein at least one of the hash tables is configured to hold a different number of slots than at least another one of the hash tables; computing a hash value based on the key; using said hash value to locate a beginning of the particular sequence of slots that correspond to said hash value; searching the particular sequence of slots for a slot holding a key value matching the key; and if a slot having a key value matching the key is found in the particular sequence of slots, but is not at the beginning of said particular sequence of slots, then moving a relative position of the key value within the particular sequence of slots toward the beginning of the particular sequence of slots.

31. (Once Amended) A method of storing a string in a lexical cache, comprising the computer-implemented steps of:

generating a key based on the string; identifying a lexical container from among a plurality of lexical containers based on a length of the key, said lexical containers are associated with respective key lengths and configured to hold respective maximum numbers of entries based on the respective key lengths; and storing the string in an entry in the lexical container based on the key, wherein at least one of the lexical containers is configured to hold a different number of entries than at least another one of the lexical containers.

32. (Once Amended) A computer-readable medium bearing instructions for storing a string in a lexical cache, said instructions arranged, when executed by one or more processors, to cause the one or more processors to perform the steps of:

generating a key based on the string;

B1 identifying a lexical container from among a plurality of lexical containers based on a length of the key, wherein the lexical containers are associated with respective key lengths and configured to hold respective maximum numbers of entries based on the respective key lengths; and

storing the string in an entry in the lexical container based on the key, wherein at least one of the lexical containers is configured to hold a different number of entries than at least another one of the lexical containers.

33. (Not Amended) The method of claim 1, wherein:

a first lexical container of the lexical containers is associated with a first key length;

a second lexical container of the lexical containers is associated with a second key length;

the first key length is less than the second key length; and

the first lexical container is configured to hold more entries than the second lexical container.

34. (Not Amended) The method of claim 31, wherein:

a first lexical container of the lexical containers is associated with a first key length;

a second lexical container of the lexical containers is associated with a second key length;

the first key length is less than the second key length; and

the first lexical container is configured to hold more entries than the second lexical container.